



PFG BEARING LIMITED



3.938 Inch | 100.025 Millimeter x 6.5 Inch | 165.1 Millimeter x 4.938 Inch | 125.425 Millimeter skf saf 22522 bearing

Bearing No. saf 22522

saf 22522 Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	33.14
EAN	7316576668975
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Tapered Adapter Sleeve
Housing Style	4 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	3/4 Inch
Relubricatable	Yes
Insert Part Number	22222 CCK/W33
Seals	Labyrinth
Housing Configuration	2 Piece Split
Inch - Metric	Inch
Other Features	Double Row Heavy Duty
Long Description	4 Bolt Pillow Block; 3-15/16" Bore; 4-15/16" Base to Center Height; Tapered Adapter Sleeve Mount; Spherical Roller Bearing; 12-5/8" Minimum



PFG BEARING LIMITED

	Bolt Spacing; 14-1/2" Bolt Spacing Maxim
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	SAF 22522
Weight / LBS	73
Nominal Bolt Center to Center	13.5 Inch 342.5 Millimeter
Bolt Spacing Minimum	12.625 Inch 320.675 Millimeter
Bolt Spacing Maximum	14.5 Inch 368.3 Millimeter
d	3.938 Inch 100.025 Millimeter
B	4.938 Inch 125.425 Millimeter
Actual Bolt Center to Center	0 Inch 0 Millimeter
D	6.5 Inch 165.1 Millimeter
bore diameter:	3.9375 in
base width:	120.65 mm
overall length:	419.10 mm
expansion type:	Non-Expansion Bearing (Fixed)
overall height:	239.40 mm
finish/coating:	Uncoated
mounting:	Four-Bolt Base
overall width:	6-1/2 in
bearing type:	Spherical Roller
seal type:	Labyrinth
bore type:	Round



PFG BEARING LIMITED

radial dynamic load capacity:	560 kN
housing construction:	Split Pillow Block
maximum rpm:	4000 RPM
base to bore centerline:	125.43 mm
lubrication type:	Lubrication Fitting
locking device:	Adapter Mount
series:	SAF
bolt center-to-center length:	344.49 mm
replacement bearing:	22222EK
d_a	100.013 mm
D_a	200 mm
C_a	62.789 mm
A_1	120.65 mm
A_2	165.1 mm
S	4.763 mm
b_a	50.006 mm
H	239.316 mm
H_1	125.425 mm
H_2	50.8 mm
J min.	320.675 mm
J max.	368.3 mm
J_1	69.85 mm
L	419.1 mm
N_1	22.225 mm
R_1	67.866 mm
R_2	31.75 mm
R_G	3/8 NPT
P_G	1/4 NPT
h	45.244 mm
Housing	SAF 522
Bearing	22222 EK
Adapter sleeve assembly	SNW 22x3.15/16



PFG BEARING LIMITED

Stabilizing ring	SR-22-19
Labyrinth ring	2 x LOR 109
End plug (suffix Y)	EPR 13
Bearing limiting speed	4000 r/min
P_{60°	149 kN
P_{90°	89 kN
P_{120°	55.6 kN
P_{150°	50.7 kN
P_{180°	60.9 kN
P_a	17.3 kN
Mass pillow block	33.1 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N · m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	232.47 g